

SOILS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

60
SHUTTLE XL



3 CYLINDER DIESEL
ENGINE

12F+12R SYNCHROMESH
SHUTTLE TRANSMISSION

HEAVY LIFT
CAPACITY

EASY FRONT AND
LOADER ATTACHMENT

HEAVY DUTY
4WD



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR



60
SHUTTLEXL

Solis



FEATURES	60 SHUTTLEXL
ITL ENGINE	
No. of cylinders / capacity (cc) / emissions level	3/ 3065/ CRDi Stage V
After treatment system	DOC + DPF
Rated engine power (kw/Hp)	43.2/58
Rated engine speed	2000
Max. torque (Nm)	250@1400 Rpm
Aspiration	Turbo charged
Intercooler	●
Air Cleaner	Dual Stage Dry Type
Block Heater	○
Updraft Exhaust Pipe	●
Downdraft Exhaust Pipe	○
Fuel tank capacity (L)	72
TRANSMISSION	
12x12 Synchro Shuttle transmission (4WD)	●
Minimum forward speed	1.3kmph
Maximum forward speed	30kmph
12x12 Synchro Shuttle transmission (4WD) with Creeper	○
Minimum forward speed	0.5kmph
Maximum forward speed	30kmph
FRONT AXLE	
2WD Front Axle	○
4WD Front Axle	●
Differential Lock	Mechanical
4WD Actuation	Mechanical
Brake Actuation	Mechanical Assist
PTO	
PTO Type	Mechanical
540/540E	●
540/1000	○
540/ground speed	○
HYDRAULIC	
Hydraulic pump flow (lpm)	45
Open center mechanical draft control	●
Top link draft sensing	●
Liftomatic system	○
Lift Capacity	2500 KG
Linkage Category	II
Self Locking Linkages	○
Max. no. of rear remotes	2/3 (Opt.)
Max. no. of Mid remotes	2
Mechanical joystick control for mid mounts with valves	1 (Opt.)
REAR HITCHES	
E-Mark Swinging Drawbar	●

FEATURES	60 SHUTTLEXL
Cuna Type Ladder Hitch	○
Semi Automatic Ladder Hitch	○
Automatic Ladder Hitch	○
TRAILER BRAKES	
Without Trailer Brakes	●
Hydraulic Trailer Brakes	○
Dual Line Pneumatic Trailer Brakes	○
ELECTRICALS (ROPS/CAB)	
Battery	110AH 800CCA
Alternator	90A/120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven On Trailer Socket	●
OPERATOR ENVIRONMENT	
Suspended platform (with ROPS)	●
Premium Driver seat	○
Tiltable & Telescopic Steering	○
Integrated Loader Joystick	○
Cabin Air Conditioning (With Cabin)	○
DIMENSIONS (ROPS/CAB)	
Wheelbase (mm)	2225
Overall Height (mm)	ROPS: 2650 - 2700 CAB: 2450 - 2500
Overall Width (mm)	1825-1950
Overall Length (mm)	3830 - 4060
Front Track Width (mm)	1525 - 1570
Rear Track Width (mm)	1420 - 1440
Ground Clearance (mm)	310 - 355
Unladen Mass (Kg)	ROPS:2780 - 3315 CAB: 3340 - 3560
Tyre Combination	9.5x24 & 14.9x28
Optional Tyre Combinations	
Bias Tyres (2WD)	7.5x16 & 16.9x28
Bias Tyres (4WD)	9.5x24 & 16.9x28
Radial Tyres (4WD)	250/85 R24 & 420/85 R28 280/85R24 AGRIMAX RT855 E 115A8/B SPL 420/85R28 AGRIMAX RT855 E 139A8/B SPL 320/70R24 AGRIMAX RT765 E 116D SPL 480/70R28 AGRIMAX RT765 E 140D SPL
Industrial Tyres (4WD)	10-16.5 & 14.9-24 12.5/80-18 & 18.4-24

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com