

SOILS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

H26



THERMO DYNAMICS
BONNET & TWIN
PROJECTOR LAMPS

MID & REAR
PTO

SEPARATE PEDAL
FOR FORWARD
& REVERSE

CRUISE
CONTROL

QUICK ATTACH
MOWER



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**

THE TOUGHEST
PERFORMER
« FOR YOUR FIELD »

H26

Solis



FEATURES	H26 (HST)
ENGINE	
Engine Type	Mitsubishi 3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the Engine Compartment, Downward Discharge
TRANSMISSION	
Drive	4 WD
Clutch	Wet Type Clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	2 Speed HST
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21.03@2660
Minimum Speed (Km/Hr)	3.18 at Low Idle 900 erpm, 8.83@rated erpm
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (RPM)	Mid PTO- 2100 RPM, Rear 540
PTO (Actuation)	Electro Hydraulic Operated
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional Hydraulic Circuit	1 DA
Hydraulic Lifting Capacity (Kg)	600
Lift Rods	Standard
Litre Per Minute (LPM)	15.0
SAFETY SWITCH	
PTO Safety	Standard

FEATURES	H26 (HST)		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
CAPACITY (LTRS)(+/-5%)			
Fuel Tank (Ltr.)	22		
TURNING RADIUS			
Without brakes (m) as per Standard Tyres	3.05 (RHS), 2.62 (LHS)		
TYRE			
Front	6.00-12		
Rear	8.30-20		
DIMENSION & WEIGHT(+/-5%)			
Weight (Kg)	1160		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (min) - 1290 (max)		
Height (mm) up to ROPS	2440		
Min Ground Clearance (mm)	215		
Front Track (mm)	880-990		
Rear Track (mm)	920-1000		
OTHERS			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with Std. Ballast	Front Weights - 2 x 15 Kg		
Trailer Hitch	Clevis Hitch (Standard)		
	Swinging Drawbar (Optional)		
	Semi Automatic Hitch		
ROPS	Standard		
OPTIONAL FEATURES			
Cabin	Heater Cabin		
TYRES			
RADIAL AGRI Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18	TURF Front Tyre: 25x8,50-14 Rear Tyre: 13.60-16	INDUSTRIAL Front Tyre: 23x8,50-12 Rear Tyre: 33x15,5-16,5	GALAXY PRO Front Tyre: 220/55R12 Rear Tyre: 280/70R16
Front Loader	Yes Optional		

DEALER STAMP



*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com