

Solis

INTRODUCING THE NEW
**BENCHMARK OF
PERFORMANCE**



50
SHUTTLE XL

S COMMAND
CENTER

S-TECH
ENGINE

TORQUE
MASTER

S-BOOST
HYDRAULICS




FEATURES	
ITL ENGINE	
No. of cylinders / capacity (cc) / emissions level	3/ 3065/ CRDi Stage V
After treatment system	DOC + DPF
Rated engine power (kw/Hp)	37.3/50
Rated engine speed	2000
Max. torque (Nm)	215@1400 Rpm
Aspiration	Turbo charged
Intercooler	●
Air Cleaner	Dual Stage Dry Type
Block Heater	○
Updraft Exhaust Pipe	●
Downdraft Exhaust Pipe	○
Fuel tank capacity (L)	72
TRANSMISSION	
12x12 Synchro Shuttle transmission (4WD)	●
Minimum forward speed	1.3kmph
Maximum forward speed	30kmph
12x12 Synchro Shuttle transmission (4WD) with Creeper	○
Minimum forward speed	0.5kmph
Maximum forward speed	30kmph
FRONT AXLE	
2WD Front Axle	○
4WD Front Axle	●
Differential Lock	Mechanical
4WD Actuation	Mechanical
Brake Actuation	Mechanical Assist
PTO	
PTO Type	Mechanical
540/540E	●
540/1000	○
540/ground speed	○
HYDRAULIC	
Hydraulic pump flow (lpm)	45
Open center mechanical draft control	●
Top link draft sensing	●
Liftomatic system	○
Lift Capacity	2500 KG
Linkage Category	II
Self Locking Linkages	○
Max. no. of rear remotes	2/3 (Opt.)
Max. no. of Mid remotes	2
Mechanical joystick control for mid mounts with valves	○

FEATURES	
REAR HITCHES	
E-Mark Swinging Drawbar	●
Cuna Type Ladder Hitch	○
Semi Automatic Ladder Hitch	○
Automatic Ladder Hitch	○
TRAILER BRAKES	
Without Trailer Brakes	●
Hydraulic Trailer Brakes	○
Dual Line Pneumatic Trailer Brakes	○
ELECTRICALS (ROPS/CAB)	
Battery	110AH 800CCA
Alternator	90A/120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven On Trailer Socket	●
OPERATOR ENVIRONMENT	
Suspended platform (with ROPS)	●
Premium Driver seat	○
Tilttable & Telescopic Steering	○
Integrated Loader Joystick	○
Cabin Air Conditioning (With Cabin)	○
DIMENSIONS (ROPS/CAB)	
Wheelbase (mm)	2225
Overall Height (mm)	2690/2480
Overall Width (mm)	1840-1880
Overall Length (mm)	3825-4055
Front Track Width (mm)	1570
Rear Track Width (mm)	1450
Ground Clearance (mm)	310
Unladen Mass (Kg)	2870
Tyre Combination	9.5x20 & 13.6x28
Optional Tyre Combinations	
Bias Tyres (2WD)	6x16 & 12.4x28
	6.0x16 & 13.6x28
	6.5x16 & 13.6x28
	7.5x16 & 14.9x28
Bias Tyres (4WD)	8.3x24 & 13.6x28
	9.5x20 & 14.9x28
Radial Tyres (4WD)	250/85R20 & 340/85R28
	280/70R18 & 380/70R28
Industrial Tyres (4WD)	10-16.5 & 14.9-24
	12.5/80-18 & 18.4-24

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221
Fax: +91- 01882-522222 | **Email:** info@solisworld.com | **URL:** www.solistractors.com