

SOILS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

75
SHUTTLE XL



4 CYLINDER STAGE V
HIGH END TORQUE ENGINE

SYNCHRO SHUTTLE
TRANSMISSION

ADVANCED HYDRAULIC
LIFT CAPACITY

S COMMAND
CENTER

MULTIPLE
TYRE OPTIONS



COST
EFFICIENT
MECHANICAL TRACTORS

MADE OF
REAL
STEEL

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER
« FOR YOUR FIELD »**

**75
SHUTTLE XL**

Solis



| FEATURES | 75 SHUTTLE XL |
|---|-----------------------|
| ITL ENGINE | |
| No. of cylinders / capacity (cc) / emissions level | 4/ 4087/ CRDi Stage V |
| After treatment system | DOC + DPF |
| Rated engine power (kw/Hp) | 55.9/75 |
| Rated engine speed | 2000 |
| Max. torque (Nm) | 340@1400 Rpm |
| Aspiration | Turbo charged |
| Intercooler | ● |
| Air Cleaner | Dual Stage Dry Type |
| Block Heater | ○ |
| Updraft Exhaust Pipe | ● |
| Downdraft Exhaust Pipe | ○ |
| Fuel tank capacity (L) | 88 |
| DEF Tank capacity (L) | - |
| TRANSMISSION | |
| 12x12 Synchro Shuttle transmission (4WD) | ● |
| Minimum forward speed | 1.22kmph |
| Maximum forward speed | 35kmph |
| 20x20 Synchro Shuttle transmission (4WD) with Super Creeper | ○ |
| Minimum forward speed | 0.25kmph |
| Maximum forward speed | 40kmph |
| FRONT AXLE | |
| 4WD Front Axle | ● |
| Differential Lock | Mechanical |
| 4WD Actuation | Electro Hydraulic |
| Brake Actuation | Hydraulic Assisted |
| PTO | |
| PTO Type | Mechanical |
| 540/540E | ● |
| 540/1000 | ○ |
| 540/ground speed | ○ |
| HYDRAULIC | |
| Hydraulic pump flow (lpm) | 65 |
| Draft Control | ● |
| Liftomatic system | ● |
| Lift Capacity | 2500 Kg / 3000 Kg (0) |
| Linkage Category | II |
| Self Locking Linkages | ○ |
| Max. no. of rear remotes | 2/3 (0) |
| Max. no. of Mid remotes | ○ |
| Mechanical joystick control for mid mounts with valves | 1 (0) |
| REAR HITCHES | |
| E-Mark Swinging Drawbar | ● |
| Semi Automatic Ladder Hitch | ○ |
| Automatic Ladder Hitch | ○ |

| FEATURES | 75 SHUTTLE XL |
|--|--|
| Cuna Type Ladder Hitch | ○ |
| TRAILER BRAKES | |
| Without Trailer Brakes | ● |
| Hydraulic Trailer Brakes | ○ |
| Dual Line Pneumatic Trailer Brakes | ○ |
| ELECTRICALS (ROPS/CAB) | |
| Battery | 130AH 800CCA |
| Alternator | ROPS: 90A / Cab: 120A |
| Button Operated Battery Cut off Switch, 3 Pinsocket, Seven On Trailer Socket | ● |
| OPERATOR ENVIRONMENT | |
| Suspended platform (with ROPS) | ● |
| Premium Driver seat | ○ |
| Tilttable & Telescopic Steering | ● |
| Integrated Loader Joystick | ○ |
| Cabin Air Conditioning (With Cabin) | ○ |
| DIMENSIONS (ROPS/CAB) | |
| Wheelbase (mm) | 2350 |
| Overall Height (mm) | ROPS: 2500 - 2730 Cab: 2490 - 2650 |
| Overall Width (mm) | ROPS: 2000 - 2050 Cab: 2050 - 2080 |
| Overall Length (mm) | ROPS: 4005 - 4230 Cab: 3915 - 4140 |
| Front Track Width (mm) | 1650-1850 |
| Rear Track Width (mm) | 1500-1700 |
| Ground Clearance (mm) | 300-420 |
| Unladen Mass (Kg) | ROPS: 3550 - 3720 CAB: 3825 - 4245 |
| Tyre Combination | 11.2x24 & 16.9x30 |
| OPTIONAL TYRE COMBINATIONS | |
| Bias Tyres (4WD) | 12.4*24 18.4*30 |
| Radial Tyres (4WD) | 280/85R24 & 420/85R30 320/85R24 & 460/85R30 320/70R24 & 480/70R30 360/85R24 & 460/85R30 |

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com